





# PROMASEAL® Profiles


Technical data	
Colour	Anthracite grey
Fire behaviour	Class E
Expansion temperature	°C approx. 190


PROMASEAL®-LX PRO 370	
Appearance	Flexible  (2)
Usage category	Class X
Expansion	mm/g 7.5 - 9.5
Expansion pressure	N/mm <sup>2</sup> 0.25 - 0.6
Material cold gas seal	TPE Thermoplastic elastomer (halogen-free)
Delivery form	Strips 2.15 m (50 pcs./box)

PROMASEAL®-LX PRO round cord	
Appearance	Flexible  (2)
Usage category	Class X
Expansion	mm/g 7.5 - 9.5
Expansion pressure	N/mm <sup>2</sup> 0.25 - 0.6
Dimensions	mm LX PRO 278 Ø appr. 8.5   LX PRO 564 Ø appr. 7.0   LX PRO 453 Ø appr. 4.5
Delivery form	Roll LX PRO 278 100 m/box   LX PRO 564 200 m/box   LX PRO 453 300 m/box

PROMASEAL®-LX PRO 545	
Appearance	Flexible  (2)
Usage category	Class X
Expansion	mm/g 7.5 - 9.5
Expansion pressure	N/mm <sup>2</sup> 0.25 - 0.6
Delivery form	Roll 100 m/box

PROMASEAL®-LX PRO 645	
Appearance	Flexible  (2)
Usage category	Class X
Expansion	mm/g 7.5 - 9.5
Expansion pressure	N/mm <sup>2</sup> 0.25 - 0.6
Delivery form	Strips 2.15 m (150 pcs./box)

PROMASEAL®-LX PRO 496	
Usage category	Class X  (2)
Expansion	mm/g 7.5 - 9.5
Expansion pressure	N/mm <sup>2</sup> 0.25 - 0.6
Material cold gas seal	TPE Thermoplastic elastomer (halogen-free)
Delivery form	Strips 2.15 m strips (150 pcs./box)

PROMASEAL®-IG4-B PRO 669	
Appearance	Flexible  (2)
Usage category	Class Z <sub>2</sub>
Expansion	mm/g 1:4 - 1:8
Expansion pressure	N/mm <sup>2</sup> 0.25 - 0.6
Delivery form	Strips 1 m strips (100 pcs./box)

### Product description

PROMASEAL® Profiles are graphite-based seals. There are two versions:

- A hot gas seal that protects against smoke and the spreading of fire in case of fire
- A combination of cold and hot gas seal, which additionally protects against draft and noise

### Properties and advantages

- The profiles can be developed and manufactured according to customer requirements
- Resistant to atmospheric effects (light, heat, frost, UV radiation, humidity<sup>(1)</sup>)
- Free from organic solvents and halogens

### Area of application

- Preventing the spread of fire and smoke between fire-resistant components and special components, in particular fire doors and gates, fire dampers and shutters and glazing

### Delivery form

- Rolls or strip goods (from the profile geometry-dependent)
- Possibly minimum order quantities are required

### Storage

- Storage temperature: 3 °C - 35 °C
- Store in dry rooms

### Test certificates and approvals

- On request, depending on the version

### Safety instructions

Please request safety information.

(1) The fire protection properties according to TR 024: 2009 are not impaired by weathering, however, direct influence from humidity can lead to optical and fastening impairments. We therefore recommend that you do not expose the product to permanent direct moisture.  
(2) Schematic diagram. Details on request.