

Promat



Technical Data Sheet

BOARD

DALFRATHERM[®]-1200 ULS

DALFRATHERM®-1200 ULS boards are manufactured utilizing the same Ultra Low Shot technology utilized throughout our DALFRATHERM® product range.

Our continuous production process with state-of-the-art drying techniques enables us to make uniform, lightweight, low shot and stable boards up to a 100mm thick.

Typical applications

- Thermal insulation for furnace lining
- High temperature back-up insulation
- General technical insulation of furnaces and technical installations
- Lining combustion chamber for domestic boilers and heaters

Benefits

- Excellent insulation performance
- Superior handling strength
- Resistant to high gas velocity erosion
- Can be used in direct flame contact
- Low shrinkage
- Excellent thermal stability
- Resistant to thermal shock
- Exonerated of carcinogenic classification under Note Q

The DALFRATHERM®-1200 ULS board is our general purpose high temperature board manufactured from low bio persistence (AES) fiber and carefully selected fillers to deliver high strength and performance in refractory linings. Another popular application is its use in domestic boilers.

All products in the DALFRATHERM® ULS product range meet the requirements specified under NOTE Q of European Regulation 1272/2008. DALFRATHERM® ULS products are exonerated from labelling requirements in Europe.

The DALFRATHERM® ULS low bio persistence range is complimented by an extensive range of refractory ceramic fiber (RCF) Boards and a range of Special Grade Boards delivering High Strength or, when

based on PCW fiber, boards for the most demanding applications.

Type

Boards made from high temperature low bio persistence (AES) insulation wool and selected fillers.

Temperature range

DALFRATHERM®-1200 ULS board has a classification temperature of 1200°C.

The maximum continuous use temperature of 1050°C is only applicable in a clean oxidizing atmosphere.

DALFRATHERM® -1200 ULS BOARD

1200°C



Grade			AES, low biopersistence
Colour			white
Classification temperature		°C (°F)	1200°C (2192°F)
Continuous use temperature		°C (°F)	1050°C (1922°F)
Density	EN 1094-4	kg/m ³	320
Compressive strength (unfired; <20mm/>20mm)	GB/T 5072	kPa	≥ 100/≥ 150
Rupture strength (unfired)	GB/T 3001	kPa	≥ 700
Linear shrinkage	GB/T 17911	%	
12h@1100°C (2012°F)			< 2
Thermal conductivity	ASTM C201	W/m.K	
200°C (392°F)			0,07
400°C (752°F)			0,09
600°C (1112°F)			0,12
800°C (1472°F)			0,16
1000° (1832°F)			0,21
1200° (2192°F)			-
Loss on Ignition	GB/T 6900	%	< 8

Availability (X = standard; Other thicknesses on special demand)

Thickness mm (inch)		L mm (inch)	W mm (inch)
10 (0,4)	X	1000 (39,37)	600 (23,62)
15 (0,59)	X	1000 (39,37)	600 (23,62)
20 (0,79)	X	1000 (39,37)	600 (23,62)
25 (0,98)	X	1000 (39,37)	600 (23,62)
50 (1,97)	X	1000 (39,37)	600 (23,62)
10 (0,4)	X	1200 (47,24)	1000 (39,37)
15 (0,59)	X	1200 (47,24)	1000 (39,37)
20 (0,79)	X	1200 (47,24)	1000 (39,37)
25 (0,98)	X	1200 (47,24)	1000 (39,37)
50 (1,97)	X	1200 (47,24)	1000 (39,37)

Promat

Etex Building Performance NV

Bormstraat 24
2830 Tiselt
Belgium
+32 2 778 12 11
industry@promat.com
www.promat.com/en/industry

Etex Building Performance GmbH

Scheifenkamp 16
40878 Ratingen
Germany
+49 2102 493 0
industry.verkauf@promat.de
www.promat.com/de/industry

Promat SpA

Via Provinciale 10
24040 Filago BG
Italy
+39 0350069500
industryITA@promat.com
www.promat.com/it-it/industry

Etex France Building Performance S.A.S

500 rue Marcel Demonque, Pôle Agroparc
84915 Avignon Cedex 9
France
+33 (0)4 32 44 44 90
industryFR@promat.com
www.promat.com/fr-fr/industry

Promat Iberica, S.A.

Calle Velázquez 47, 6° izquierda
28001 Madrid
Spain
+34 917 811 550
info@promat.es
www.promat.com/en/industry

Promat TOP Sp. z o.o.

ul.Przeclawska 8
03-879 Warszawa
Poland
+48 22 212 22 95
ei.pl@etexgroup.com
www.promat.com/pl-pl/industry

Promat s.r.o.

V. P. Čkalova 784/22
160 00 Praha 6 - Bubeneč
Czech Republic
+420 224 390 811
pavel.dvorak@etexgroup.com
www.promat.com/cs-cz/industry

Eternit Baltic

J. Dalinkevičiaus str. 2H
Naujoji Akmenė 85118
Lithuania
+370 42 55 68 49
industry@promat.com
www.promat.com/en/industry

Etex Sverige

Hästvägen 4A
212 35 Malmö
Sweden
+44 (0)800 588 4444
industryuk@promat.co.uk
www.promat.com/en-gb/inds

Promat UK Limited

B1 The Innovation Centre
Pilsworth Road - Heywood Distribution Park
Heywood Lancashire OL10 2TS
United Kingdom
+44 (0)800 588 4444
industryuk@promat.co.uk
www.promat.com/en-gb/inds

Promat Inc.

1731 Fred Lawson Drive
Maryville, TN 37801
USA
+1 888 681 0155
industryUS@promat.com
www.promat.com/en-us/industry

Marley Building Systems

2 Setchell Rd
Roodekop
Germiston 1401
South Africa
+27 (0)11 389 4500,
industry@promat.com
www.promat.com/en/industry

Promat Fire Protection LLC

Plot # 597 - 921 - Dubai Investment Park 2
Dubai
United Arab Emirates
+971 4 885 3070

Promat Japan Corporation

Hulic Kakigaracho Bldg., 1-28-5
Nihonbashi Kakigara-cho, Chuo-ku,
Tokyo 103-0014
Japan
+81-3-3808-2820
sales@promat.jp
www.promat.com/ja-jp/industry

Promat Malaysia

Sdn. Bhd. ,Unit 19-02-01, Level 2,
Wisma Tune, No 19, Lorong Dungun, Damansara
Heights
50490 Kuala Lumpur
Malaysia
+603 2095 8555 ext. 140
www.promat.com/en/industry

Promat International Ltd (Korea Branch)

11F, 117, Namdaemun-ro
Jung-gu, Seoul, 04522
South Korea
+82 70 7794 8216
www.promat.com/en/industry

Promat Fire & Insulation Private Ltd

Global Business Park Unit No. 605, 6th Floor, Tower B,
Mehrauli Gurgaon Road, Sector 26, Gurgaon,
122 002 Haryana
India
+91-124-434-6865
promatindia@etexgroup.com
www.promat.com/en/industry

All data contained in this publication are provided in good faith and are correct at the time of printing. Data are typical values, are representative of production and are subject to normal production fluctuations, they should not be deemed to constitute or imply any warranty of performance, the user is held responsible for determining the suitability of the products for the given application. Errors and omissions excepted. Promat accepts no legal responsibility for use or reliance upon this data. All drawings and representations remain our exclusive property and cannot be used, totally or in part, without our prior written approval. Excerpts, reproductions, copies, etc. of our publications require our prior approval. This publication renders all previous ones invalid. Our terms of delivery and payment apply in the event of any claim. Promat and Microtherm are registered trademarks.

© Copyright Etex NV, Brussels, Belgium.

All rights reserved. 2020-06

Etex Industry c/o Microtherm N.V.
Industriepark-Noord 1
9100 Sint-Niklaas
Belgium
+32 (0)3 760 19 80
info@promat-industry.com
www.promat-industry.com

